

## PRODUCT SPECIFICATIONS

4S255-S24, 4S255-S48, 4S255-D48, 4S255-48N


# Shielded Flat QUICKPORT™ Patch Panels

## APPLICATION

Shielded Flat QUICKPORT Patch Panels protect critical data from EMI (electromagnetic interference) and RFI (radio frequency interference). This makes them ideal for use in health care, manufacturing, and other environments where EMI and RFI may be present. Shielded Flat QUICKPORT Patch Panels are available in 24 and 48 ports and include a high-density option for applications where space is limited.



4S255-S24



4S255-S48



4S255-D48



4S255-48N

## SPECIFICATION

Patch panels shall be available in either 24- or 48-port configurations and shield data from electromagnetic and radio frequency interference. Panels shall have a black powder coat finish with white silk screening. Panels shall meet or exceed ANSI/TIA-568, ANSI/TIA-1096-A, ANSI/TIA 607, and IEC 60603-7.

## FEATURES & BENEFITS

- Shielding provides EMI/RFI protection and data security
- Panels feature a stainless-steel plate to provide grounding continuity between connectors and panel
- High-density panel includes hardware to accept standards-compliant grounding connectors
- Standard-density panels include cable management bar
- 4S255-D48 offers 48 ports in only 1RU of rack space

## DESIGN CONSIDERATIONS

- Verify rack is grounded according to commercial building grounding and bonding requirements for telecommunications
- Mounts on 19-inch equipment racks

## STANDARDS & REGULATIONS

- ANSI/TIA 568.0-E
- ANSI/TIA-1096-A
- IEC 60603-7
- ETL with third-party verification
- ANSI/TIA 607

## MECHANICAL SPECIFICATIONS

Dimensions: See page 2

Materials: 4S255-Sxx – 16 AWG; black powder coating  
4S255-48N – 16 AWG; black powder coating  
4S255-D48 – 20 AWG; black powder coating

Temp. (Storage): -40 °C to +70 °C (-40 °F to +158 °F)

Temp. (Operating): -10 °C to +60 °C (+14 °F to +140 °F)

Temp. (Installation): Refer to cable installation temperature

Humidity (Max.): 95% relative humidity, non-condensing

## COUNTRY OF ORIGIN


4S255-S24: Taiwan  
4S255-D48: Taiwan  
4S255-S48: Taiwan  
4S255-48N: Taiwan

## WARRANTY INFORMATION

For Leviton product warranties, go to [Leviton.com/ns/warranty](http://Leviton.com/ns/warranty)

4S255-S24, 4S255-S48, 4S255-D48, 4S255-48N

**PRODUCT SPECIFICATIONS**  
**4S255-S24, 4S255-S48, 4S255-D48, 4S255-48N**



**4S255-S24, 4S255-S48, 4S255-D48, 4S255-48N**

PART NUMBER	
Description	Part No.
Shielded Flat QUICKPORT™ Patch Panel, 24 ports, 1RU with cable management bar	4S255-S24
Shielded Flat QUICKPORT Patch Panel, 48 ports, 1RU	4S255-D48
Shielded Flat QUICKPORT Patch Panel, 48 ports, 2RU with cable management bar	4S255-S48
Shielded Flat QUICKPORT Patch Panel with Vertical Numbering, 48 ports, 2RU with cable management bar	4S255-48N

For further support information, visit [Leviton.com/ns/support](http://Leviton.com/ns/support)